MY24 MAVERICK R X RS 999T DCT with SMART-SHOX



HIGHLIGHTS

- 77 in. (195.6 cm) 4 Link Trailing arm with aluminum HD tall knuckle
- Smart-Lok[™] front differential
- FOX† 3.0 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
- · 10.25 in. (26 cm) touchscreen display
- 32 in. (81.3 cm) ITP Tenacity XNR tires
- 16 in. (40.6 cm) FlowFormed Beadlock wheels
- · Front and rear camera
- · Telescopic steering wheel with infotainment controls
- Full roof
- Full skid plate
- · 4-point harness with shoulder pads
- · Premium high-performance LED headlights
- · Can-Am LED signature
- · Center dashboard storage with cell phone holder
- · X-package graphics/seats
- · 1,700 W Magneto

LITOINE	
Туре	179 kW (240 hp), Rotax 999T DCT engine, 999cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Rotax DCT, 7 Speed with High & Low range
Drive Train	Lockable front differential with exclusive Smart- Lok. True 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV/ 4WD TRAIL
Power Steering	Gen 2 Tri-mode DPS High torque

ENGINE

SUSPENSIONS Forged Aluminum heavy duty Tall Knuckle -Front Suspension Double A-arm with sway bar / 25 in. (63.5 cm) travel FOX† 2.5 PODIUM† Piggyback with bypass and Front Shocks Smart-Shox Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound) 4 Link Trailing arm with Forged Aluminum Rear Suspension heavy duty tall knuckle / 26 in. (66 cm) travel Rear Shocks FOX† 3.0 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)

TIRES / WHEELS	
Front & Rear Tires	XPS Track Force 32 x 10 x 16 in. (81.3 x 25.4 x 40.6 cm)
Wheels	16 in. (40.6 cm) Aluminum FlowFormed Beadlock

BRAKES	
Front	32 mm hydraulic tripple piston caliper with a 265 mm disc
Rear	30 mm hydraulic twin piston caliper with a 255 mm disc

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	2,250 lb (1,020 kg)
Chassis / Cage	High strengh steel (Dual phase) steel tubing and stampings
LxWxH	140 x 78.1 x 71.5 in. (355.6 x 198.5 x 181.5 cm)
Wheelbase	108 in. (274.3 cm)
Ground Clearance	17 in. (43.2 cm)
Rack Capacity	200 lbs (90 kg)
Storage Capacity	Total: 2.1 gal (8.1 L)
Fuel Capacity	13.2 Gal (50 L)

EATURES

Gauge	4.5 in. (11.4 cm) wide digital display with
	keypad & 10.25 in. (26 cm) touchscreen display
Instrumentation	USB A (Charging port & Communication port) DC outlet (10-A)
Magneto	1,700 W
Anti-theft System	RF Digitally Encoded Security System
	(D.E.S.S.™) with Start/Stop button
Lighting	Premium high-performance LED headlights
	Can-Am LED signature
Winch	4,500 lb winch ready bumper (not installed)
Protection	Full roof
	Premium half doors
	Front lower deflector
	Front / Rear anchor
	Full plastic skid plate

WARRANTY

warrantv





